

產品規格 AS568-001

AS568A	Millimeters				Inches			
SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)	±
001	0.74	±0.10	1.02	±0.08	0.029	±0.004	0.040	±0.003
002	1.07		1.27		0.042		0.050	
003	1.42		1.53		0.056		0.060	
004	1.78	±0.13	1.78		0.070	±0.005	0.070	
005	2.57		1.78		0.101		0.070	
006	2.9		1.78		0.114		0.070	
007	3.69		1.78		0.145		0.070	
008	4.47		1.78		0.176		0.070	
009	5.29		1.78		0.208		0.070	
010	6.07		1.78		0.239		0.070	
011	7.65		1.78		0.301		0.070	
012	9.25		1.78		0.364		0.070	
013	10.82		1.78		0.426		0.070	
014	12.42		1.78		0.489		0.070	
015	14	±0.18	1.78		0.551	±0.007	0.070	
016	15.6	±0.23	1.78		0.614	±0.009	0.070	
017	17.17		1.78		0.676		0.070	
018	18.77		1.78		0.739		0.070	
019	20.35		1.78		0.801		0.070	
020	21.95		1.78		0.864		0.070	
021	23.52		1.78		0.926		0.070	
022	25.12	±0.25	1.78		0.989	±0.010	0.070	
023	26.7		1.78		1.051		0.070	
024	28.3	±0.26	1.78		1.114	±0.010	0.070	

Directions

AS568 is a standardized specification for O-rings established by the Society of Automotive Engineers (SAE). This specification is used widely in various industries for sealing applications. These tolerances help maintain a proper seal under various pressures and temperatures.

產品規格 AS568-001

AS568A	Millimeters				Inches			
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)
025	29.87	±0.28	1.78	±0.08	1.176	±0.011	0.070	±0.003
026	31.47		1.78		1.239		0.070	
027	33.05		1.78		1.301		0.070	
028	34.65	±0.33	1.78		1.364	±0.013	0.070	
029	37.82		1.78		1.489		0.070	
030	41		1.78		1.614		0.070	
031	44.17	±0.38	1.78		1.739	±0.015	0.070	
032	47.35		1.78		1.864		0.070	
033	50.52	±0.46	1.78		1.989	±0.018	0.070	
034	53.7		1.78		2.114		0.070	
035	56.87		1.78		2.239		0.070	
036	60.05		1.78		2.364		0.070	
037	63.22		1.78		2.489		0.070	
038	66.4	±0.51	1.78		2.614	±0.020	0.070	
039	69.57		1.78		2.739		0.070	
040	72.75		1.78		2.864		0.070	
041	75.92	±0.61	1.78		2.989	±0.024	0.070	
042	82.27		1.78		3.239		0.070	
043	88.62		1.78		3.489		0.070	
044	94.97	±0.69	1.78		3.739	±0.027	0.070	
045	101.32		1.78		3.989		0.070	
046	107.67	±0.76	1.78		4.239	±0.030	0.070	
047	114.02		1.78		4.489		0.070	
048	120.37		1.78		4.739		0.070	
049	126.72	±0.94	1.78		4.989	±0.037	0.070	
050	133.07		1.78		5.239		0.070	

產品規格 AS568-102

AS568A	Millimeters				Inches			
	SIZE	ID(內徑)	±	W(線徑)	±	ID(內徑)	±	W(線徑)
102	1.25	±0.13	2.62	±0.08	0.049	±0.005	0.103	±0.003
103	2.06				0.081		0.103	
104	2.85				0.112		0.103	
105	3.64				0.143		0.103	
106	4.42				0.174		0.103	
107	5.24				0.206		0.103	
108	6.02				0.237		0.103	
109	7.6				0.299		0.103	
110	9.2				0.362		0.103	
111	10.77				0.424		0.103	
112	12.37	0.487	0.103					
113	13.95	±0.18	2.62	0.549	±0.007	0.103	±0.003	
114	15.55	±0.23	2.62	0.612	±0.009	0.103		
115	17.12		2.62	0.674		0.103		
116	18.72		2.62	0.737		0.103		
117	20.3	±0.26	2.62	0.799	±0.010	0.103		
118	21.9		2.62	0.862		0.103		
119	23.47		2.62	0.924		0.103		
120	25.07		2.62	0.987		0.103		
121	26.65		2.62	1.049		0.103		
122	28.25	2.62	1.112	0.103				
123	29.82	±0.31	2.62	1.174	±0.012	0.103		
124	31.42		2.62	1.237		0.103		
125	33		2.62	1.299		0.103		
126	34.6		2.62	1.362		0.103		
127	36.17		2.62	1.424		0.103		
128	37.77		2.62	1.487		0.103		
129	39.35	±0.38	2.62	1.549	±0.015	0.103		
130	40.95		2.62	1.612		0.103		
131	42.52		2.62	1.674		0.103		
132	44.12		2.62	1.737		0.103		
133	45.7		2.62	1.799		0.103		
134	47.3	±0.39	2.62	1.862	±0.015	0.103		
135	48.9	±0.43	2.62	1.925	±0.017	0.103		
136	50.47		2.62	1.987		0.103		
137	52.07		2.62	2.050		0.103		
138	53.65		2.62	2.112		0.103		
139	55.25		2.62	2.175		0.103		
140	56.82		2.62	2.237		0.103		

產品規格 AS568-102

AS568A	Millimeters				Inches			
	SIZE	ID(內徑)	±	W(線徑)	±	ID(內徑)	±	W(線徑)
141	58.42	±0.51	2.62	±0.08	2.300	±0.020	0.103	±0.003
142	60		2.62		2.362		0.103	
143	61.6		2.62		2.425		0.103	
144	63.17		2.62		2.487		0.103	
145	64.77		2.62		2.550		0.103	
146	66.35		2.62		2.612		0.103	
147	67.95	±0.56	2.62		2.675	±0.022	0.103	
148	69.52		2.62		2.737		0.103	
149	71.12		2.62		2.800		0.103	
150	72.7		2.62		2.862		0.103	
151	75.87	±0.61	2.62		2.987	±0.024	0.103	
152	82.22		2.62		3.237		0.103	
153	88.57		2.62		3.487		0.103	
154	94.92	±0.71	2.62		3.737	±0.028	0.103	
155	101.27		2.62		3.987		0.103	
156	107.62	±0.76	2.62		4.237	±0.030	0.103	
157	113.97		2.62		4.487		0.103	
158	120.32		2.62		4.737		0.103	
159	126.67	±0.89	2.62	4.987	±0.035	0.103		
160	133.02		2.62	5.237		0.103		
161	139.37		2.62	5.487		0.103		
162	145.72		2.62	5.737		0.103		
163	152.07		2.62	5.987		0.103		
164	158.42	±1.02	2.62	6.237	±0.040	0.103		
165	164.77		2.62	6.487		0.103		
166	171.12		2.62	6.737		0.103		
167	177.47		2.62	6.987		0.103		
168	183.82	±1.14	2.62	7.237	±0.045	0.103		
169	190.17		2.62	7.487		0.103		
170	196.52		2.62	7.737		0.103		
171	202.87		2.62	7.987		0.103		
172	209.22	±1.27	2.62	8.237	±0.050	0.103		
173	215.57		2.62	8.487		0.103		
174	221.92		2.62	8.737		0.103		
175	228.27		2.62	8.987		0.103		
176	234.62	±1.4	2.62	9.237	±0.055	0.103		
177	240.97		2.62	9.487		0.103		
178	247.32		2.62	9.737		0.103		

產品規格 AS568-201

AS568A	Millimeters				Inches			
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)
201	4.35	±0.13	3.53	±0.10	0.171	±0.005	0.139	±0.004
202	5.95				0.234			
203	7.52				0.296			
204	9.12				0.359			
205	10.7				0.421			
206	12.3				0.484			
207	13.87	±0.18	3.53		0.546	±0.007	0.139	
208	15.47	±0.23	3.53		0.609	±0.009	0.139	
209	17.04				0.671			
210	18.65	±0.25	3.53		0.734	±0.010	0.139	
211	20.22				0.796			
212	21.82	±0.26	3.53		0.859	±0.010	0.139	
213	23.4				0.921			
214	25				0.984			
215	26.57				1.046			
216	28.17	±0.31	3.53		1.109	±0.012	0.139	
217	29.75				1.171			
218	31.35				1.234			
219	32.92				1.296			
220	34.52				1.359			
221	36.1				1.421			
222	37.69	±0.38	3.53		1.484	±0.015	0.139	
223	40.87				1.609			
224	44.04				1.734			
225	47.22	±0.46	3.53		1.859	±0.018	0.139	
226	50.4				1.984			
227	53.57				2.109			
228	56.75	±0.50	3.53		2.234	±0.020	0.139	

產品規格 AS568-201

AS568A	Millimeters				Inches			
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)
229	59.92	±0.51	3.53	±0.10	2.359	±0.020	0.139	±0.004
230	63.1				2.484			
231	66.27				2.609			
232	69.44	±0.61	3.53		2.734	±0.024	0.139	
233	72.62				2.859			
234	75.79				2.984			
235	78.97				3.109			
236	82.14				3.234			
237	85.32				3.359			
238	88.49				3.484			
239	91.67				3.609			
240	94.84	±0.71	3.53		3.734	±0.028	0.139	
241	98.02				3.859			
242	101.19				3.984			
243	104.37				4.109			
244	107.54	±0.77	3.53		4.234	±0.030	0.139	
245	110.72				4.359			
246	113.89				4.484			
247	117.07				4.609			
248	120.25	±0.89	3.53		4.734	±0.035	0.139	
249	123.42				4.859			
250	126.59				4.984			
251	129.77				5.109			
252	132.94				5.234			
253	136.12				5.359			
254	139.29				5.484			
255	142.47				5.609			
256	145.64				5.734			
257	148.82				5.859			
258	151.99	5.984						

產品規格 AS568-201

AS568A	Millimeters				Inches			
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)
259	158.35	±1.02	3.53	±0.10	6.234	±0.040	0.139	±0.004
260	164.7				6.484			
261	171.05				6.734			
262	177.4				6.984			
263	183.75	±1.15	3.53		7.234	±0.045	0.139	
264	190.1				7.484			
265	196.45				7.734			
266	202.8				7.984			
267	209.14	±1.27	3.53		8.234	±0.050	0.139	
268	215.49				8.484			
269	221.84				8.734			
270	228.19				8.984			
271	234.55	±1.4	3.53		9.234	±0.055	0.139	
272	240.9				9.484			
273	247.25				9.734			
274	253.6				9.984			
275	266.3				10.484			
276	278.99	±1.65	3.53		10.984	±0.065	0.139	
277	291.69				11.484			
278	304.39				11.984			
279	329.79			12.984				
280	355.19			13.984				
281	380.59	±1.91	3.53	14.984	±0.075	0.139		
282	405.26			15.955				
283	430.66	±2.03	3.53	16.955	±0.080	0.139		
284	456.06	±2.16	3.53	17.955	±0.085	0.139		

產品規格 AS568-309

AS568A	Millimeters				Inches			
	SIZE	ID(內徑)	±	W(線徑)	±	ID(內徑)	±	W(線徑)
309	10.47	±0.13	5.33	±0.13	0.412	±0.005	0.210	±0.005
310	12.07		5.33		0.475		0.210	
311	13.64	±0.18	5.33		0.537	±0.007	0.210	
312	15.24	±0.23	5.33		0.600	±0.009	0.210	
313	16.82		5.33		0.662		0.210	
314	18.42	±0.26	5.33		0.725	±0.010	0.210	
315	19.99		5.33		0.787		0.210	
316	21.59		5.33		0.850		0.210	
317	23.17		5.33		0.912		0.210	
318	24.77		5.33		0.975		0.210	
319	26.34		5.33		1.037		0.210	
320	27.94	±0.30	5.33		1.100	±0.012	0.210	
321	29.52	±0.31	5.33		1.162	±0.012	0.210	
322	31.12		5.33		1.225		0.210	
323	32.69		5.33		1.287		0.210	
324	34.29		5.33		1.350		0.210	
325	37.47	±0.39	5.33		1.475	±0.015	0.210	
326	40.64		5.33		1.600		0.210	
327	43.82		5.33		1.725		0.210	
328	46.99		5.33		1.850		0.210	
329	50.17	±0.45	5.33		1.975	±0.018	0.210	
330	53.34	±0.46	5.33		2.100	±0.018	0.210	
331	56.52		5.33		2.225		0.210	
332	59.69		5.33		2.350		0.210	
333	62.87	±0.50	5.33		2.475	±0.020	0.210	
334	66.04	±0.51	5.33		2.600	±0.020	0.210	
335	69.22		5.33		2.725		0.210	
336	72.39		5.33		2.850		0.210	
337	75.57	±0.61	5.33		2.975	±0.024	0.210	
338	78.74		5.33		3.100		0.210	
339	81.92		5.33		3.225		0.210	
340	85.09		5.33		3.350		0.210	
341	88.27		5.33		3.475		0.210	

產品規格 AS568-309

AS568A	Millimeters				Inches			
	SIZE	ID(內徑)	±	W(線徑)	±	ID(內徑)	±	W(線徑)
342	91.44	±0.71	5.33	±0.13	3.600	±0.028	0.210	±0.005
343	94.62		5.33		3.725		0.210	
344	97.79		5.33		3.850		0.210	
345	100.97	±0.72	5.33	3.975	±0.028	0.210		
346	104.14		5.33	4.100		0.210		
347	107.32	±0.77	5.33	4.225	±0.030	0.210		
348	110.49		5.33	4.350		0.210		
349	113.67		5.33	4.475		0.210		
350	116.84		5.33	4.600		0.210		
351	120.02		5.33	4.725		0.210		
352	123.19		5.33	4.850		0.210		
353	126.37	±0.93	5.33	4.975	±0.037	0.210		
354	129.53		5.33	5.100		0.210		
355	132.72	±0.94	5.33	5.225	±0.037	0.210		
356	135.89		5.33	5.350		0.210		
357	139.07		5.33	5.475		0.210		
358	142.24		5.33	5.600		0.210		
359	145.42		5.33	5.725		0.210		
360	148.59		5.33	5.850		0.210		
361	151.77		5.33	5.975		0.210		
362	158.12	±1.02	5.33	6.225	±0.040	0.210		
363	164.47		5.33	6.475		0.210		
364	170.82		5.33	6.725		0.210		
365	177.17	±1.15	5.33	6.975	±0.045	0.210		
366	183.52		5.33	7.225		0.210		
367	189.87		5.33	7.475		0.210		
368	196.22		5.33	7.725		0.210		
369	202.57		5.33	7.975		0.210		

產品規格 AS568-309

AS568A	Millimeters				Inches			
	SIZE	ID(內徑)	±	W(線徑)	±	ID(內徑)	±	W(線徑)
370	208.92	±1.27	5.33	±0.13	8.225	±0.050	0.210	±0.005
371	215.27				8.475			
372	221.62				8.725			
373	227.97				8.975			
374	234.32	±1.40	5.33		9.225	±0.055	0.210	
375	240.67				9.475			
376	247.02				9.725			
377	253.37				9.975			
378	266.07	±1.52	5.33		10.475	±0.060	0.210	
379	278.77	±1.53	5.33		10.975	±0.060	0.210	
380	291.47	±1.66	5.33		11.475	±0.065	0.210	
381	304.17				11.975			
382	329.57				12.975			
383	354.97	±1.78	5.33		13.975	±0.070	0.210	
384	380.37				14.975			
385	405.26	±1.91	5.33		15.955	±0.075	0.210	
386	430.66	±2.03	5.33		16.955	±0.080	0.210	
387	456.06	±2.16	5.33		17.955	±0.085	0.210	
388	481.46	±2.29	5.33		18.955	±0.090	0.210	
389	506.86	±2.41	5.33		19.955	±0.095	0.210	
390	532.26			20.955				
391	557.66	±2.54	5.33	21.955	±0.100	0.210		
392	582.68	±2.67	5.33	22.940	±0.105	0.210		
393	608.07	±2.81	5.33	23.940	±0.111	0.210		
394	633.48	±2.92	5.33	24.940	±0.115	0.210		
395	658.88	±3.04	5.33	25.940	±0.120	0.210		

產品規格 AS568-425

AS568A	Millimeters				Inches			
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)
425	113.67	±0.84	6.99	±0.16	4.475	±0.033	0.275	±0.006
426	116.84				4.600			
427	120.02				4.725			
428	123.19				4.850			
429	126.37	±0.93	6.99	4.975	±0.037	0.275		
430	129.54	±0.94	6.99	5.100	±0.037	0.275		
431	132.72		6.99	5.225		0.275		
432	135.89		6.99	5.350		0.275		
433	139.07		6.99	5.475		0.275		
434	142.24		6.99	5.600		0.275		
435	145.42		6.99	5.725		0.275		
436	148.59		6.99	5.850		0.275		
437	151.77		6.99	5.975		0.275		
438	158.12	±1.02	6.99	6.225	±0.040	0.275		
439	164.47		6.99	6.475		0.275		
440	170.82		6.99	6.725		0.275		
441	177.17		6.99	6.975		0.275		
442	183.52	±1.15	6.99	7.225	±0.045	0.275		
443	189.87		6.99	7.475		0.275		
444	196.22		6.99	7.725		0.275		
445	202.57		6.99	7.975		0.275		
446	215.27	±1.40	6.99	8.475	±0.055	0.275		
447	227.96		6.99	8.975		0.275		
448	240.67		6.99	9.475		0.275		
449	253.37		6.99	9.975		0.275		
450	266.07	±1.52	6.99	10.475	±0.060	0.275		

產品規格 AS568-425

AS568A	Millimeters				Inches			
SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)	±
451	278.77	±1.53	6.99	±0.16	10.975	±0.060	0.275	±0.006
452	291.47		6.99		11.475		0.275	
453	304.17		6.99		11.975		0.275	
454	316.87		6.99		12.475		0.275	
455	329.57		6.99		12.975		0.275	
456	342.27	±1.78	6.99		13.475	±0.070	0.275	
457	354.97		6.99		13.975		0.275	
458	367.67		6.99		14.475		0.275	
459	380.37		6.99		14.975		0.275	
460	393.07	±1.91	6.99		15.475	±0.075	0.275	
461	405.26		6.99		15.955		0.275	
462	417.96		6.99		16.455		0.275	
463	430.66	±2.03	6.99		16.955	±0.080	0.275	
464	443.36	±2.16	6.99		17.455	±0.085	0.275	
465	456.06		6.99		17.955		0.275	
466	468.76		6.99		18.455		0.275	
467	481.46	±2.29	6.99		18.955	±0.090	0.275	
468	494.16		6.99		19.455		0.275	
469	506.86	±2.41	6.99		19.955	±0.095	0.275	
470	532.46		6.99		20.963		0.275	
471	557.66	±2.54	6.99		21.955	±0.100	0.275	
472	582.68	±2.67	6.99		22.940	±0.105	0.275	
473	608.08	±2.80	6.99		23.940	±0.110	0.275	
474	633.48	±2.92	6.99		24.940	±0.115	0.275	
475	658.88	±3.04	6.99		25.940	±0.120	0.275	

產品規格 AS568-901

AS568A	Millimeters				Inches				
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)	±
901	4.7	±0.13		1.43	±0.08	0.185	±0.005	0.056	±0.003
902	6.07			1.63		0.239		0.064	
903	7.65			1.63		0.301		0.064	
904	8.92			1.83		0.351		0.072	
905	10.52			1.83		0.414		0.072	
906	11.89			1.98		0.468		0.078	
907	13.46	±0.18	±0.08	2.09	±0.007	0.530	±0.009	0.082	±0.003
908	16.36	±0.23		2.21		0.644		0.087	
909	17.93			2.47		0.706		0.097	
910	19.18			2.47		0.755		0.097	
911	21.92			2.95		0.863		0.116	
912	23.47			2.95		0.924		0.116	
913	25.05		±0.26	±0.1	2.95	±0.010	0.986	±0.012	0.116
914	26.6	2.95			1.047		0.116		
916	29.75	2.95			1.171		0.116		
918	34.42	±0.31			2.95		1.355		0.116
920	37.47	±0.36	±0.1	3	±0.014	1.475	±0.018	0.118	±0.004
924	43.69			3		1.720		0.118	
928	53.09	±0.45	±0.1	3	±0.018	2.090	±0.019	0.118	±0.004
932	59.37	±0.47		3		2.337		0.118	

產品規格 P series

JIS B 2401	Millimeters				Inches					
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)	±	
P 3	2.8	±0.14	1.9	±0.08	0.110	±0.006	0.075	±0.003		
P 4	3.8				0.150		0.075			
P 5	4.8	±0.15	1.9		0.189	±0.006	0.075			
P 6	5.8				0.228		0.075			
P 7	6.8	±0.16	1.9		0.268	±0.006	0.075			
P 8	7.8				0.307		0.075			
P 9	8.8	±0.17	1.9		0.346	±0.007	0.075			
P 10	9.8				0.386		0.075			
P 10A	9.8	±0.17	2.4		±0.09	0.386	±0.007		0.094	±0.004
P 11	10.8	±0.18	2.4			0.425	±0.007		0.094	
P 11.2	11			0.433		0.094				
P 12	11.8	±0.19	2.4	0.465		±0.007	0.094			
P 12.5	12.3			0.484			0.094			
P 14	13.8			0.543			0.094			
P 15	14.8	±0.20	2.4	0.583		±0.008	0.094			
P 16	15.8			0.622			0.094			
P 18	17.8	±0.21	2.4	0.701		±0.008	0.094			
P 20	19.8	±0.22	2.4	0.780		±0.009	0.094			
P 21	20.8	±0.23	2.4	0.819		±0.009	0.094			
P 22	21.8	±0.24	2.4	0.858		±0.009	0.094			

Directions

JIS (Japanese Industrial Standards) are a set of standards used for industrial activities in Japan. They are created and maintained by the Japanese Industrial Standards Committee (JISC). The primary purpose of JIS standards is to ensure the quality, safety, and interoperability of products and services. These standards cover a wide range of industries, including materials, products, machinery, electronic devices, data processing, and services. By adhering to JIS standards, companies can facilitate both domestic and international trade.

產品規格 P series

JIS B 2401	Millimeters				Inches			
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)
P 22A	21.7	±0.24	3.5	±0.10	0.854	±0.009	0.138	±0.004
P 22.4	22.1		3.5		0.870		0.138	
P 24	23.7		3.5		0.933		0.138	
P 25	24.7	±0.25	3.5		0.972	±0.010	0.138	
P 25.5	25.2		3.5		0.992		0.138	
P 26	25.7	±0.26	3.5		1.012	±0.010	0.138	
P 28	27.7	±0.28	3.5		1.091	±0.011	0.138	
P 29	28.7	±0.29	3.5		1.130	±0.011	0.138	
P 29.5	29.2		3.5		1.150		0.138	
P 30	29.7		3.5		1.169		0.138	
P 31	30.7	±0.30	3.5		1.209	±0.012	0.138	
P 31.5	31.2	±0.31	3.5		1.228	±0.012	0.138	
P 32	31.7		3.5		1.248		0.138	
P 34	33.7	±0.33	3.5		1.327	±0.013	0.138	
P 35	34.7	±0.34	3.5		1.366	±0.013	0.138	
P 35.5	35.2		3.5		1.386		0.138	
P 36	35.7		3.5		1.406		0.138	
P 38	37.7	±0.37	3.5		1.484	±0.015	0.138	
P 39	38.7		3.5		1.524		0.138	
P 40	39.7		3.5		1.563		0.138	
P 41	40.7	±0.38	3.5	1.602	±0.015	0.138		
P 42	41.7	±0.39	3.5	1.642	±0.015	0.138		
P 44	43.7	±0.41	3.5	1.720	±0.016	0.138		
P 45	44.7		3.5	1.760		0.138		
P 46	45.7	±0.42	3.5	1.799	±0.017	0.138		
P 48	47.7	±0.44	3.5	1.878	±0.017	0.138		
P 49	48.7	±0.45	3.5	1.917	±0.018	0.138		
P 50	49.7		3.5	1.957		0.138		

產品規格 P series

JIS B 2401	Millimeters				Inches			
SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)	±
P 48A	47.6	±0.44	5.7	±0.13	1.874	±0.017	0.224	±0.005
P 50A	49.6	±0.45	5.7		1.953	±0.018	0.224	
P 52	51.6	±0.47	5.7		2.031	±0.019	0.224	
P 53	52.6	±0.48	5.7		2.071	±0.019	0.224	
P 55	54.6	±0.49	5.7		2.150	±0.019	0.224	
P 56	55.6	±0.50	5.7		2.189	±0.020	0.224	
P 58	57.6	±0.52	5.7		2.268	±0.020	0.224	
P 60	59.6	±0.53	5.7		2.346	±0.021	0.224	
P 62	61.6	±0.55	5.7		2.425	±0.022	0.224	
P 63	62.6	±0.56	5.7		2.465	±0.022	0.224	
P 65	64.6	±0.57	5.7		2.543	±0.022	0.224	
P 67	66.6	±0.59	5.7		2.622	±0.023	0.224	
P 70	69.6	±0.61	5.7		2.740	±0.024	0.224	
P 71	70.6	±0.62	5.7		2.780	±0.024	0.224	
P 75	74.6	±0.65	5.7		2.937	±0.026	0.224	
P 80	79.6	±0.69	5.7		3.134	±0.027	0.224	
P 85	84.6	±0.73	5.7		3.331	±0.029	0.224	
P 90	89.6	±0.77	5.7		3.528	±0.030	0.224	
P 95	94.6	±0.81	5.7		3.724	±0.032	0.224	
P 100	99.6	±0.84	5.7		3.921	±0.033	0.224	
P 102	101.6	±0.85	5.7		4.000	±0.033	0.224	
P 105	104.6	±0.87	5.7		4.118	±0.034	0.224	
P 110	109.6	±0.91	5.7		4.315	±0.036	0.224	
P 112	111.6	±0.92	5.7		4.394	±0.036	0.224	
P 115	114.6	±0.94	5.7		4.512	±0.037	0.224	
P 120	119.6	±0.98	5.7		4.709	±0.039	0.224	
P 125	124.6	±1.01	5.7		4.906	±0.040	0.224	
P 130	129.6	±1.05	5.7		5.102	±0.041	0.224	
P 132	131.6	±1.06	5.7		5.181	±0.042	0.224	
P 135	134.6	±1.09	5.7		5.299	±0.043	0.224	
P 140	139.6	±1.12	5.7	5.496	±0.044	0.224		
P 145	144.6	±1.16	5.7	5.693	±0.046	0.224		
P 150	149.6	±1.19	5.7	5.890	±0.047	0.224		

產品規格 P series

JIS B 2401	Millimeters				Inches			
SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)	±
P 150A	149.5	±1.19	8.4	±0.15	5.886	±0.047	0.331	±0.006
P 155	154.5	±1.23	8.4		6.083	±0.048	0.331	
P 160	159.5	±1.26	8.4		6.280	±0.050	0.331	
P 165	164.5	±1.30	8.4		6.476	±0.051	0.331	
P 170	169.5	±1.33	8.4		6.673	±0.052	0.331	
P 175	174.5	±1.37	8.4		6.870	±0.054	0.331	
P 180	179.5	±1.40	8.4		7.067	±0.055	0.331	
P 185	184.5	±1.44	8.4		7.264	±0.057	0.331	
P 190	189.5	±1.48	8.4		7.461	±0.058	0.331	
P 195	194.5	±1.51	8.4		7.657	±0.059	0.331	
P 200	199.5	±1.55	8.4		7.854	±0.061	0.331	
P 205	204.5	±1.58	8.4		8.051	±0.062	0.331	
P 209	208.5	±1.61	8.4		8.209	±0.063	0.331	
P 210	209.5	±1.62	8.4		8.248	±0.064	0.331	
P 215	214.5	±1.65	8.4		8.445	±0.065	0.331	
P 220	219.5	±1.68	8.4		8.642	±0.066	0.331	
P 225	224.5	±1.71	8.4		8.839	±0.067	0.331	
P 230	229.5	±1.75	8.4		9.035	±0.069	0.331	
P 235	234.5	±1.78	8.4		9.232	±0.070	0.331	
P 240	239.5	±1.81	8.4		9.429	±0.071	0.331	
P 245	244.5	±1.84	8.4		9.626	±0.072	0.331	
P 250	249.5	±1.88	8.4		9.823	±0.074	0.331	
P 255	254.5	±1.91	8.4		10.020	±0.075	0.331	
P 260	259.5	±1.94	8.4		10.217	±0.076	0.331	
P 265	264.5	±1.97	8.4		10.413	±0.078	0.331	
P 270	269.5	±2.01	8.4		10.610	±0.079	0.331	
P 275	274.5	±2.04	8.4		10.807	±0.080	0.331	
P 280	279.5	±2.07	8.4		11.004	±0.081	0.331	
P 285	284.5	±2.10	8.4		11.201	±0.083	0.331	
P 290	289.5	±2.14	8.4		11.398	±0.084	0.331	
P 295	294.5	±2.17	8.4		11.594	±0.085	0.331	
P 300	299.5	±2.20	8.4		11.791	±0.087	0.331	
P 315	314.5	±2.30	8.4		12.382	±0.091	0.331	
P 320	319.5	±2.33	8.4		12.579	±0.092	0.331	
P 335	334.5	±2.42	8.4		13.169	±0.095	0.331	
P 340	339.5	±2.45	8.4		13.366	±0.096	0.331	
P 355	354.5	±2.54	8.4		13.957	±0.100	0.331	
P 360	359.5	±2.57	8.4		14.154	±0.089	0.331	
P 375	374.5	±2.67	8.4	14.744	±0.105	0.331		
P 380	379.5	±2.70	8.4	14.941	±0.106	0.331		
P 385	384.5	±2.73	8.4	15.138	±0.107	0.331		

產品規格 G series

JIS B 2401	Millimeters				Inches			
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)
G 25	24.4	±0.25	3.1	±0.10	0.961	±0.010	0.122	±0.004
G 30	29.4	±0.29	3.1		1.157	±0.011	0.122	
G 35	34.4	±0.33	3.1		1.354	±0.013	0.122	
G 40	39.4	±0.37	3.1		1.551	±0.015	0.122	
G 45	44.4	±0.41	3.1		1.748	±0.016	0.122	
G 50	49.4	±0.45	3.1		1.945	±0.018	0.122	
G 55	54.4	±0.49	3.1		2.142	±0.019	0.122	
G 60	59.4	±0.53	3.1		2.339	±0.021	0.122	
G 65	64.4	±0.57	3.1		2.535	±0.022	0.122	
G 70	69.4	±0.61	3.1		2.732	±0.024	0.122	
G 75	74.4	±0.65	3.1		2.929	±0.026	0.122	
G 80	79.4	±0.69	3.1		3.126	±0.027	0.122	
G 85	84.4	±0.73	3.1		3.323	±0.029	0.122	
G 90	89.4	±0.77	3.1		3.520	±0.030	0.122	
G 95	94.4	±0.81	3.1		3.717	±0.032	0.122	
G 100	99.4	±0.85	3.1		3.913	±0.033	0.122	
G 105	104.4	±0.87	3.1		4.110	±0.034	0.122	
G 110	109.4	±0.91	3.1		4.307	±0.036	0.122	
G 115	114.4	±0.94	3.1		4.504	±0.037	0.122	
G 120	119.4	±0.98	3.1		4.701	±0.039	0.122	
G 125	124.4	±1.01	3.1		4.898	±0.040	0.122	
G 130	129.4	±1.05	3.1		5.094	±0.041	0.122	
G 135	134.4	±1.08	3.1		5.291	±0.043	0.122	
G 140	139.4	±1.12	3.1		5.488	±0.044	0.122	
G 145	144.4	±1.16	3.1	5.685	±0.046	0.122		

產品規格 G series

JIS B 2401	Millimeters				Inches			
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)
G 150	149.3	±1.19	5.7	±0.13	5.878	±0.047	0.224	±0.005
G 155	154.3	±1.23	5.7		6.075	±0.048	0.224	
G 160	159.3	±1.26	5.7		6.272	±0.050	0.224	
G 165	164.3	±1.30	5.7		6.469	±0.051	0.224	
G 170	169.3	±1.33	5.7		6.665	±0.052	0.224	
G 175	174.3	±1.37	5.7		6.862	±0.054	0.224	
G 180	179.3	±1.40	5.7		7.059	±0.055	0.224	
G 185	184.3	±1.44	5.7		7.256	±0.057	0.224	
G 190	189.3	±1.47	5.7		7.453	±0.058	0.224	
G 195	194.3	±1.51	5.7		7.650	±0.059	0.224	
G 200	199.3	±1.55	5.7		7.846	±0.061	0.224	
*G 205	204.3	±1.58	5.7		8.043	±0.062	0.224	
G 210	209.3	±1.61	5.7		8.240	±0.063	0.224	
*G 215	214.3	±1.65	5.7		8.437	±0.065	0.224	
G 220	219.3	±1.68	5.7		8.634	±0.066	0.224	
*G 225	224.3	±1.71	5.7		8.831	±0.067	0.224	
G 230	229.3	±1.73	5.7		9.028	±0.068	0.224	
*G 235	234.3	±1.78	5.7		9.224	±0.070	0.224	
G 240	239.3	±1.81	5.7		9.421	±0.071	0.224	
G 250	249.3	±1.88	5.7		9.815	±0.074	0.224	
*G 255	254.3	±1.91	5.7		10.012	±0.075	0.224	
G 260	259.3	±1.94	5.7		10.209	±0.076	0.224	
*G 265	264.3	±1.97	5.7		10.406	±0.078	0.224	
G 270	269.3	±2.01	5.7		10.602	±0.079	0.224	
*G 275	274.3	±2.04	5.7		10.799	±0.080	0.224	
G 280	279.3	±2.07	5.7		10.996	±0.081	0.224	
G 290	289.3	±2.14	5.7		11.390	±0.084	0.224	
G 300	299.3	±2.20	5.7		11.783	±0.087	0.224	
*G 305	304.3	±2.24	5.7		11.980	±0.088	0.224	
*G 310	309.3	±2.27	5.7		12.177	±0.089	0.224	
*G 315	314.3	±2.30	5.7		12.374	±0.091	0.224	
*G 320	319.3	±2.33	5.7		12.571	±0.092	0.224	
*G 330	329.3	±2.39	5.7		12.965	±0.094	0.224	
*G 345	344.3	±2.48	5.7		13.555	±0.098	0.224	
*G 355	354.3	±2.54	5.7		13.949	±0.100	0.224	
*G 380	379.3	±2.70	5.7		14.933	±0.106	0.224	
*G 385	384.3	±2.73	5.7		15.130	±0.107	0.224	
*G 400	399.3	±2.82	5.7		15.720	±0.111	0.224	

產品規格 S series

JIS B 2401	Millimeters				Inches			
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)
S 3	2.5	±0.15	1.5	±0.10	0.098	±0.006	0.059	±0.004
S 4	3.5		1.5		0.138		0.059	
S 5	4.5		1.5		0.177		0.059	
S 6	5.5		1.5		0.217		0.059	
S 7	6.5		1.5		0.256		0.059	
S 8	7.5		1.5		0.295		0.059	
S 9	8.5		1.5		0.335		0.059	
S 10	9.5		1.5		0.374		0.059	
S 11.2	10.7		1.5		0.421		0.059	
S 12	11.5		1.5		0.453		0.059	
S 12.5	12		1.5		0.472		0.059	
S 14	13.5		1.5		0.531		0.059	
S 15	14.5		1.5		0.571		0.059	
S 16	15.5		1.5		0.610		0.059	
S 18	17.5		1.5		0.689		0.059	
S 20	19.5		1.5		0.768		0.059	
S 22	21.5		2		0.846		0.059	
S 22.4	21.9		2		0.862		0.079	
S 24	23.5		2		0.925		0.079	
S 25	24.5		2		0.965		0.079	
S 26	25.5		2		1.004		0.079	
S 28	27.5		2		1.083		0.079	
S 29	28.5		2		1.122		0.079	
S 30	29.5		2		1.161		0.079	
S 31.5	31		2		1.220		0.079	
S 32	31.5		2		1.240		0.079	
S 34	33.5		2		1.319		0.079	
S 35	34.5		2		1.358		0.079	
S 35.5	35		2		1.378		0.079	
S 36	35.5		2		1.398		0.079	
S 38	37.5		2		1.476		0.079	
S 39	38.5		2		1.516		0.079	
S 40	39.5		2		1.555		0.079	

產品規格 S series

JIS B 2401	Millimeters				Inches			
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)
S 42	41.5	±0.25	2	±0.10	1.634	±0.010	0.079	±0.004
S 44	43.5							
S 45	44.5							
S 46	45.5							
S 48	47.5							
S 50	49.5							
S 53	52.5							
S 55	54.5							
S 56	55.5							
S 60	59.5							
S 63	62.5							
S 65	64.5							
S 67	66.5							
S 70	69.5							
S 71	70.5	±0.40	2	±0.10	2.776	±0.016	0.079	±0.004
S 75	74.5							
S 80	79.5							
S 85	84.5							
S 90	89.5							
S 95	94.5							
S 100	99.5							
S 105	104.5							
S 110	109.5							
S 112	111.5							
S 115	114.5							
S 120	119.5							
S 125	124.5							
S 130	129.5				±0.60			
S 132	131.5							
S 135	134.5							
S 140	139.5							
S 145	144.5							
S 150	149.5							
S 150	149.5							

產品規格 V series

JIS B 2401	Millimeters				Inches			
	SIZE	ID (內徑)	±	W (線徑)	±	ID (內徑)	±	W (線徑)
V 15	14.5	0.20	4	±0.10	0.571	±0.008	0.157	±0.004
V 24	23.5	0.24	4		0.925	±0.009	0.157	
*V 34	33.5	0.33	4		1.319	±0.013	0.157	
V 40	39.5	0.37	4		1.555	±0.015	0.157	
*V 45	44.5	0.49	4		1.752	±0.019	0.157	
*V 50	49.5		4		1.949		0.157	
V 55	54.5		4		2.146		0.157	
V 70	69	0.61	4		2.717	±0.024	0.157	
*V 75	74	0.72	4		2.913	±0.028	0.157	
V 85	84		4		3.307		0.157	
*V 90	89	0.83	4		3.504	±0.033	0.157	
*V 95	94		4		3.701		0.157	
V 100	99		4		3.898		0.157	
*V 110	109	0.97	4		4.291	±0.038	0.157	
V 120	119		4		4.685		0.157	
*V 130	129	1.18	4		5.079	±0.046	0.157	
*V 140	138.5		4		5.453		0.157	
V 150	148.5		4		5.846		0.157	
V 175	173	1.36	4	6.811	±0.054	0.157		
V 225	222.5	1.70	6	8.760	±0.067	0.236	±0.006	
*V 230	227.5	1.95	6	8.957	±0.077	0.236		
*V 235	232.5		6	9.154		0.236		
*V 240	237.5		6	9.350		0.236		
*V 245	242.5		6	9.547		0.236		
*V 250	247.5		6	9.744		0.236		
*V 255	252.5	2.02	6	9.941	±0.080	0.236		
V 275	272		6	10.709		0.236		
*V 305	302	2.34	6	11.890	±0.092	0.236		
V 325	321.5		6	12.657		0.236		
*V 335	331.5	2.51	6	13.051	±0.099	0.236		
V 380	376	2.68	6	14.803	±0.106	0.236		
*V 390	386	2.83	6	15.197	±0.111	0.236		
V 430	425.5	2.99	6	16.752	±0.118	0.236		
V 585	579	3.92	10	22.795	±0.154	0.394	±0.012	
V 640	633.5	4.24	10	24.941	±0.167	0.394		
V 690	683	4.54	10	26.890	±0.179	0.394		
V 740	732.5	4.83	10	28.839	±0.190	0.394		
V 790	782	5.12	10	30.787	±0.202	0.394		
V 845	836.5	5.44	10	32.933	±0.214	0.394		
V 950	940.5	6.06	10	37.028	±0.239	0.394		
V 1055	1044	6.67	10	41.102	±0.263	0.394		